



U24-002-C

HOBO ?????/???????

??

????????????????????±5,000 ?S/cm????????????????

Important Information

??HOBOWare Pro ?????U-DTW-1 ?????Base-U-4 ??USB??
????????????????

Supported Measurements

??/??, ??

Features

- ?????????
- ?????????
- ?????????100?55,000??/??
- ?????????
- HOBOWare Pro?????/????????????1978??????PSS-78????????
- USB????????
- ??HOBOWare Pro????????
- ????????? tarnishing????????

What's in the box

- HOBOWare Pro U24-002-C ?????
- ?????

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- Email sales@onsetcomp.com
- Call 1-508-759-9500
- In U.S. toll free 1-800-564-4377
- Fax 1-508-759-9100

Onset Computer Corporation
470 MacArthur Boulevard
Bourne, MA 02532

Technical Support (8am to 5pm ET, Monday through Friday)

- Contact Product Support www.onsetcomp.com/support/contact
- Call 1-508-759-9500
- In U.S. toll free 1-877-564-4377

HOBO ????/???? (U24-002-C) Specifications

??	
???	Actual Conductivity, Temperature, Specific Conductance at 25C (calculated), Salinity (calculated using PSS-78, the Practical Salinity Scale 1978)
??????	????100 ~ 10,000 μS/cm ????5,000 ~ 55,000 μS/cm
?????? - ????	5°C?35°C (41???95???)
??????	????100 ~ 10,000 μS/cm ????5,000 ~ 55,000 μS/cm ?????????? 0
??????	-2°C?36°C (28°?97???)
????????????????????	??????? 3% ? 50 μS/cm???? ??????? 5%???????? ±3,000 μS/cm ?????????????????
??????	2 μS/cm????
????	25°C?77°F?? ±0.1°C?±0.2°F?
????	0.01?? (0.02??)
????	???????? 12%???????????????????????????????? HOBOWare ?????????????
????	???? 90% ??? 1 ?
????	-2°C ~ 36°C?28°F ~ 97°F????
??	???????????? 18,500 ????????????? 11,500 ????????? 64 KB?
???	1 ?? 18 ????????????? 8 ?????????
????	?? ±1 ??
????	3 ??? 1 ?????????
????	70? (225??)
??	193 ??6.82 ?????????-59.8 ??-2.11 ?????????
??	?? 3.18 cm × ? 16.5 cm?? 6.3 mm ????? 1.25" × ? 6.5"¾" ????
??????	Delrin@????????????????????????????????——????????????
????	IP68

