



MX2201

HOBO Pendant MX ???????

?????????

??HOBObconnect??Windows???

Important Information

????????????Windows????HOBObconnect????????????????HOBObconnect????

????????????????????????????????????LI-COR Cloud® IoT ?????????? HOBOblink??? MX ??????



Compatible with
HOBObconnect® ????

Supported Measurements

????, ??, ??

Features

- ??????????????????
- ??????
- ?????????96,000?????
- ?????30??100???
- ????????
- ??????????????
- LED?????????????????
- ?????HOBObconnect????
- $\pm 0.5^{\circ}\text{C}$? $\pm 0.9^{\circ}\text{F}$???

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- Email sales@onsetcomp.com
- Call 1-508-759-9500
- In U.S. toll free 1-800-564-4377
- Fax 1-508-759-9100

Onset Computer Corporation
470 MacArthur Boulevard
Bourne, MA 02532

Technical Support (8am to 5pm ET, Monday through Friday)

- Contact Product Support www.onsetcomp.com/support/contact
- Call 1-508-759-9500
- In U.S. toll free 1-877-564-4377

HOBO Pendant MX (MX2201) Specifications

MX2201/MX2202	
	-20°C 70°C (-4°F 158°F)
	-20°C 50°C (-4°F 122°F)
	±0.5°C -20° 70°C (±0.9°F -4° 158°F)
	0.04 (0.072)
	0.1°C (0.18°F)
	1%/100% 90% 17%
	90% 7%

(MX2202)	
	0 167,731 (0 15,582)
	±10% 2

	-20°C 70°C (-4°F 158°F)
	2G (0.072)
	30.5 (100)
	1 (0)
	30.5 (100)
	118
	25°C ±1 (77°F ±1)
	CR2032 3V
	25°C 77°F 1 2
	25°C 77°F 1 2
	96,000
	45
	EPDM O
	3.35 × 5.64 × 1.8 (1.32 × 2.22 × 0.69)
	12.75 (0.45)
	IP68

