



MX2202

HOBO Pendant MX ??/???????

?????????

???????/????????????????????????HOBOnconnect????????????????????Windows???

Important Information

?????????Windows????HOBOnconnect????????????????HOBOnconnect????
????????????????????LI-COR Cloud® IoT ?????????? HOBOLink??? MX ?????



Compatible with
HOBOnconnect® ????

Supported Measurements

?????, ??

Features

- ??????????????????????
- ??????????????????????
- ???????1??
- ???????96,000?????
- ?????30??100???
- ????????
- ????????????
- LED???????????????
- ?????HOBOnconnect????
- ?????±0.5°C?±0.9°F????????????±10%

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- Email sales@onsetcomp.com
- Call 1-508-759-9500
- In U.S. toll free 1-800-564-4377
- Fax 1-508-759-9100

Technical Support (8am to 5pm ET, Monday through Friday)

- Contact Product Support www.onsetcomp.com/support/contact
- Call 1-508-759-9500
- In U.S. toll free 1-877-564-4377

Onset Computer Corporation
470 MacArthur Boulevard
Bourne, MA 02532

HOBO Pendant MX 2201/2202 (MX2202) Specifications

MX2201/MX2202

Temp Range	-20°C to 70°C (???) (??-4??158??) -20°C to 50°C (??) (-4??122???)
Temp Accuracy	±0.5°C/-20°C to 70°C (±0.5°C/-4??158°F)
Temp Resolution	0.04°C (0.072°F)
Temp Stability	±0.1°C (<0.18°F/h)
Temp Response	1 m/s (???) 90% (???) 17?? (???) 90%

MX2202

Temp Range	0 to 167,731?? (0 to 15,582???)
Temp Accuracy	±10% (???)

MX2202

Temp Range	-20°C to 70°C (-4??158???)
Temp Accuracy	±0.5°C (0.072°F)
Temp Resolution	0.305? (100??)
Temp Stability	±1? (0 ??)
Temp Response	30.5?? (100??)
Temp Response	Bluetooth Smart?
Temp Response	1 ?? 18 ??
Temp Response	25°C ±1? (77°F ±1?)
Temp Response	CR2032 3V (???)
Temp Response	25°C (77°F) (???) 1 (???) 1 (???) 25°C to 77°F (???) 1 (???) 1 (???) (???) 1 (???) 1 (???) (???) 1 (???) 1 (???)
Temp Response	96,000 ??
Temp Response	45 (???)
Temp Response	EPDM (???) O (???)
Temp Response	3.35×5.64×1.8?? (1.32 x 2.22 x 0.69 ??)
Temp Response	12.75? (0.45 ??)
Temp Response	IP68

