



CX603

InTemp 365????????

????????????????????

??GXP??

Important Information

???????????????????? CX5001 ?????????????? 100 ???30.5 ??????????????????



Compatible with
InTemp????
????®
????

InTemp Wi-Fi/????????

Supported Measurements

??

Features

- ??IATA????
- 3?NIST????????????????
- ?????
- ???????????????21 CFR?11????????
- ????—????????
- ?????????????
- ?????????????

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- 1-508-743-3309 (US & International)
- +45 6154 5745 (EMEA)

Technical Support (8am to 5pm ET, Monday through Friday)

- Email InTempHelp@onsetcomp.com
- Contact Support online www.onsetcomp.com/intemp/contact/support

Onset Computer Corporation
470 MacArthur Boulevard
Bourne, MA 02532

InTemp 365 Specifications (CX603)

Operating Temperature	
Operating Temperature Range	-95°C to 50°C / -139°F to 122°F
Accuracy	±1.5°C / -95°C to -40°C (±2.7°F / -139°F to -40°F) ±1.0°C / -40°C to 10°C (±1.8°F / -40°F to 14°F) ±0.5°C / 10°C to 50°C (±0.9°F / 14°F to 122°F)
Resolution	25°C / 0.013°C / 77°F / 0.023°F
Calibration	NIST traceable @ -70°C to 10°C / 5°C
Self-Heating	1.5 mW (4.92 mW)
Response Time	31.75 s to 1.25 s (4.78 s to 0.188 s)

Physical Characteristics	
Operating Temperature	-30°C to 50°C / -22°F to 122°F
Dimensions	1.7 x 0.7 x 0.4 in
Weight	30.5 g / 100 mg
Material	Stainless Steel
Finish	Polished
Part Number	365
Lead Time	1 week
Minimum Order	18 units
Power Supply	CR2450 3V coin cell battery (1 year life) or InTemp Connect (5 year life)
Memory	16,000 readings
Display	30 character LCD
Size	6.9 x 4.5 x 1.1 in / 2.71 x 1.76 x 0.42 in
Weight	25.5 g / 0.90 oz
Protection	IP65

Compliance

Meets RTCA DO160G 21H

