


SD-TEMP-01 • SD-TEMP-06 • SD-TEMP-20 • SD-TEMP-50



??????/?/???????

??? HOBO MX1104 ? MX1105 ?????????????/?/????????????????????????????????

Supported Measurements

????, ????, ??, ??

Features

- ?????????????????
- ?????????????????????
- ?????-40°C?100°C?-40°F?212°F?
- ?0°C?50°C?????±0.15°C??32°F?122°F?????±0.27°F?
- ??0.3??1????1.8??6????6.1??20????15.2??50???????

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- Email sales@onsetcomp.com
- Call 1-508-759-9500
- In U.S. toll free 1-800-564-4377
- Fax 1-508-759-9100

Onset Computer Corporation
470 MacArthur Boulevard
Bourne, MA 02532

Technical Support (8am to 5pm ET, Monday through Friday)

- Contact Product Support www.onsetcomp.com/support/contact
- Call 1-508-759-9500
- In U.S. toll free 1-877-564-4377

SD-TEMP-xx Specifications

Operating Temperature	-40° ? 50°C (-40° ? 122°F) -40° ? 100°C (-40° ? 212°F)
Storage Temperature	0° ? 50°C (32° ? 122°F) ±0.15°C (±0.27°F) 2.3 ? (0.9 ?) A
Humidity	25°C 0.002? (0.003°77777777)
Shock	<0.1°C (<0.2°F)
Wind Speed	1 m/s (2.2 mph) 90% 2 ?
Wind Direction	90% 30 ?
Pressure	50°C (122°F) 1 ?
Altitude	
Dimensions	5.1×33? (0.2 x 1.3 ?)
Weight	SD-TEMP-01: 0.3 m (1 ft) SD-TEMP-06: 1.8 m (6 ft) SD-TEMP-20: 5.1 m (20 ft) SD-TEMP-50: 15.2 m (50 ft)